

## YL60Wp, Yingli Solar

Yingli's 60 watt photovoltaic module is designed for large electrical power requirements. With a 25 year warranty, the YL60 has superb durability to withstand rigorous operating conditions. Ideal for grid-connected and remote power systems, the YL60 offers high usable power per square foot of solar array.

- ◆ Solar Cell: High efficiency crystalline solar cell. Even if under the weak light, the solar module can produce maximum power output.
- ◆ Tempered glass: Anti-reflecting coating and high transmission rate glass increase the power output and mechanical strength of solar module.
- ◆ EVA and TPT: Using high quality EVA and TPT to prevent destroying and water.
- ◆ Al frame: Without screw, corner connection. 6 holes on the frame can be installed easily.
- ◆ Junction box: Multi function junction box with water proof.
- ◆ Long lifetime:  $\geq 25$  years; Less power decrease.
- ◆ Good performance of preventing from atrocious weather such as wind and hails.
- ◆ Resisting moisture and etching effectively, not effect by geology.

- World-class Product and Service
- Complete Production Chain
- PV Manufacturer from China



# YL60Wp, Yingli Solar

- World-class Product and Service
- Complete Production Chain
- PV Manufacturer from China

## ELECTRICAL PARAMETER

Module type	60(17)PR770×660
Cell	Poly-crystal silicon
No. of Cells and Connections	36 in series
Maximum Power (Pm)	60W±3%
Maximum Power Voltage (Vpm)	17.5V
Maximum Power Current (Ipm)	3.43 A
Open Circuit Voltage (Voc)	22.0V
Short Circuit Current (Isc)	3.8A

(\* (STC) Standard Test Conditions: 25°C, 1 KW/m<sup>2</sup>, AM 1.5)

## INSTALLATION DIMENSIONS

## MECHANICAL CHARACTERISTIC

Dimensions (H×W×D)	770×660×35mm
Weight	7.3Kg
Area	0.5 m <sup>2</sup>

( Cable Length 900mm provide by clients' requirement )

## TEMPERATURE COEFFICIENTS

Power	T <sub>k</sub> (Wp)	-0.45%/°C
Open Circuit Voltage	T <sub>k</sub> (Voc)	-0.37%/°C
Short Circuit Current	T <sub>k</sub> (Isc)	+0.06%/°C

## ABSOLUTE MAXIMUM LIMITS

Max System Voltage	V600	
Module Operating Temperature	°C	-45—+85
Wind Velocity	Km/h	130
Noct	°C	46±2

## IV CURVES

20070824.03.Rev01.E



Yingli Energy ( Beijing ) Co., Ltd.

A-15 Floor No.8 Chaoyang Men St.N. Beijing China (100026)

Tel: +86(10)65546068-8022 Fax: +86(10) 65541878